

STR-DA3400ES

► <http://www.sony.co.uk>

This document was created on
18-Nov-2008

Bring incredible HD video and digital audio into your living room with this powerful 7.1 receiver. Built with the latest technologies to complement Blu-ray™ and featuring an on-board menu system for effortless 1080p (HD) upscaling of all video sources.



Variations

STR-DA3400ES



Features

Please be aware that the features/specifications can differ from country to country.

- 7.1 channel High Definition Multimedia Interface (HDMI™) receiver with 100W x 7 (700W) total power output
- HDMI™ "Active Intelligence" can detect and receive the best possible A/V signals from all connected devices, making connection and performance as simple as plugging in a single cable
- Experience thrilling surround sound with Dolby® Digital + / Dolby® TrueHD and dts® (dtsHD) decoding
- Built-in upscaler generates a 1080p signal via HDMI™ cable giving you superb picture quality on your HD TV and minimising the number of connections needed

Useful Links

► Product support
► <http://www.sony.co.uk>

- Xross Media Bar™ Inspired menu system uses icons and an easy to follow "tree" system
- BRAVIA Sync for simple, one touch integrated control over your BRAVIA TV and other compatible products with only one remote
- Optimised for High Definition playback with 4 HDMI™ inputs - offering the complete Blu-ray™ Disc viewing experience
- AM / FM tuner with RDS and 60 station pre-set
- Digital Cinema Sound for a true "at the movies" audio experience
- DCAC - one-push automatic sound set-up for flexible speaker placement and optimum sound quality
- 8 channel Linear PCM for true High Definition sound
- Easily release digital music stored on your PC, mp3 player or Bluetooth® mobile phone with the Sony DIGITAL MEDIA PORT
- Portable Audio Enhancer function boosts quality of compressed music such as mp3 files
- Night Mode with Dialogue Enhancer keeps speech clear while limiting the volume of sudden sound effects - ideal for late night viewing
- A/V Sync for perfect sound and image synchronisation

Technical specifications

Amplifier

| | |
|---|-----------------------|
| Model Name | STR-DA3400ES |
| 8Ohms 20-20kHz | 100W + 100W |
| (8Ohms 20-20kHz) THD | 0.09% |
| Number of amp. channels | 7ch |
| Bi-AMP | YES |
| Type | Analog |
| 4 Ohm / 8 Ohm Switching | YES (In Menu) |
| DSP | Titanium |
| OP processing | NO |
| Analog Down Mix | NO |
| Equalizer (F / C / Sur / Sur B) Bass, Mid, Treble | B,T / B,T / B,T / B,T |
| Subwoofer X`Over | 17 points (40-200Hz) |
| Analog Direct | YES |
| Pureness Control | NO |
| Sound Field Link (w Lock) | YES (YES) |
| Sound Field Program (Movie) | 4 |
| Sound Field Program (Music) | 6 |
| Sound Field Program (A.F.D) | 3 (7) |
| Sound Field Program (2ch) | 2 |
| Sound Field Program (Headphone) | 4 |
| Personal AUDIO Enhancer | YES |
| Cinema Studio EX. A / B / C mode | YES |
| Night Mode | YES |
| Digital Concert Hall | NO |
| Speaker Selector | A / B, A+B |
| Speaker Terminal | Screw (Ni) |
| Headphone Out | YES (Gold) |

I / Os

| | |
|---|------------------------|
| Front Input | AV (Gold) + Opt |
| DIGITAL MEDIA PORT | 1 |
| Audio In (Incl. TV CEC) / Out(excl. tuner) / TV (CEC) | 4 / 1 / YES |
| A / V In / Out (S-Video I / O): Including Front AV | 5 / 1 (0/0) |
| Monitor Out (S-Video Out) | 1 (0) |
| Component Video In / Out (Pass through) | 3 / 1 |
| Ethernet | NO |
| Phono (MM) | YES |
| Multi-ch In | 1 (7.1) |
| Pre Out | 7.1 (SB:Stereo, SW x1) |
| HDMI™ In / Out (Front In) | 4/1 |
| Opt. IN / OUT / TV (CEC) : inc Front & TV (CEC) | 4 / 1 / YES |
| Coax. | 3 / 0 |
| Digital Input Assign | YES |

HDMI™ Spec

| | |
|---------------------------|-----|
| DSD | NO |
| HATS | NO |
| BRAVIA Sync (CEC Control) | YES |

Decoding Format

| | |
|--|-------------------|
| DTS HD / Dolby®TruHD / Dolby® Digital+ | YES / YES / YES |
| LPCM (2CH / 5.1CH / 7.1CH) thru HDMI™ | YES / YES / YES |
| Dolby® Digital / DTS | YES / YES |
| Dolby® Digital EX | YES |
| DTS-ES (MATRIX6.1 / DISCRETE6.1) | YES (YES / YES) |
| DTS 96 / 24 | YES |
| DTS NEO:6 | YES |
| Dolby® Prologic | YES |
| Dolby® Prologic II | YES |
| Dolby® Prologic IIx | YES |
| Dolby® Dual Mono | YES |
| 96k / 24Bit PCM | YES |
| Neural - THX Surround | YES(225,227 only) |

Tuner

| | |
|-------------------------------|---------------|
| RDS | YES |
| Preset Channel (XM / FM / AM) | TTL60 (30/30) |
| Station Name | YES |
| Auto Tuning | YES |
| Direct Tuning | YES (RM) |

Video Features

| | |
|---|------------------------|
| HDMI™ Quality 1080p | YES |
| HDMI™ Quality 1080 / 24p | YES |
| HDMI™ Quality Deep Color | YES |
| HDMI™ Quality x.v.Color (xvYCC) | YES |
| Upscaling (Analog->Component / HDMI™, HDMI™->HDMI™) | YES / YES, NO |
| Video Up Converter (To S / Component / HDMI™) | NO / Component / HDMI™ |
| Video Down Converter (Analog) | YES |
| A / V SYNC (Variable / Fixed) | YES (Variable) |
| Auto Mode | YES |
| Time (msec) | 300 |
| Sampling Frequency (Up To 192kHz / 96kHz / 48kHz) | 192 |
| Assignable HDMI™ Video IN | YES |
| Assignable Component Video IN | YES |

DCAC (Digital Cinema Auto Calibration)

| | |
|---------------------|--------|
| DCAC (DSP / UCOM) | SILVER |
| Band | 6 |
| Mic (STEREO / MONO) | Mono |

CIS & Control features

| | |
|---|----|
| Multi-Room (Pin Jack out w Vol) | NO |
| 2nd A | NO |
| 2nd V | NO |
| 3rd A | NO |
| 3rd V | NO |
| Video Up Scaling / GUI (for Zone2) | NO |
| Amp Relocation (7.1ch -> 5.1ch + 2.0ch) | NO |
| 2nd / 3rd Zone ON / OFF Switch | NO |
| EXT Video IN (PinP) | NO |
| RS-232C for control | NO |
| 12V Trigger | NO |
| Control S | NO |
| IR Repeat (In / Out) | NO |
| S-Link/Control S (M-bus) | NO |
| Control A1 II | NO |
| Mega CD Control | NO |
| DSS Control | NO |

Network Features

| | |
|----------------|----|
| DLNA Client | NO |
| Internet Radio | NO |
| PC Connection | NO |

General

| | |
|---------------------------------|---|
| Panel | Alumi / ES Basic |
| Remote Commander | PP+Learn+Macro, RM-AAL018, Simple RM, RM-AAU039 |
| Display | 10 digit dot matrix |
| Multi Channel Decoding Blue LED | YES |
| DCS LED | YES |
| Sleep Timer | YES |
| GUI / OSD | YES |
| GUI Blending | YES(up to Component) |
| Pin Jack | Nickel |
| Detachable AC | YES |
| AC Outlet (Switched) | NO |
| Power Requirement | 230V 50 / 60Hz |
| Power Consumption (W) | 360 |
| Power Stand By (W) | 0.7 |
| Dimension (WxHxD) (mm) | 430 x 157.5 x 388 |
| Weight (Kg) | 12.5 |

Carton

| | |
|---------------|-----------------|
| Outer (WxHxD) | 529 x 278 x 472 |
| Weight (kg) | 16 |
